

Typ V30-EX  
 Model V30-EX


For loads difficult to access, or where loads have to be lifted, where working on the load itself is not practical, we recommend our EX jack series (without own hydraulic unit) for remote operation with a hydraulic hand pump. Two hydr. jacks can be operated with the hydr. hand pump PV or the electric pump PE (see page 11/12). This allows the load capacity to be doubled. For the model V30-EX we recommend our electric pump PE for remote operation.

<b>Technische Daten</b> <i>Technical data</i>	<b>V30-EX</b>
Artikelnummer <i>item number</i>	11140
Volltraglast <i>full load capacity</i>	300 kN (30 t)
Arbeitsdruck <i>working pressure</i>	420 bar
Kleinste Ansetzhöhe mittels Sicherheits-Hebelasche <i>minimum loading height using safety toe</i>	40 mm
Hubhöhe <i>lifting height</i>	156 mm
Verstellbarkeit der Sicherheits-Hebelasche <i>adjustable range of safety toe</i>	2 x
Ansetzhöhe mittels Kopfplatte <i>loading height using top plate</i>	330 mm
Außenmaße (L x B x H) <i>overall dimensions (L x W x H)</i>	468 x 400 x 330 mm
Eigengewicht <i>tare weight</i>	105 kg