

The Unilifter U6 is an all-purpose toe jack for vertical/horizontal use. Due to its shape the jack will not tilt, if used in horizontal position.

- Rugged design
- Outstanding stability because all components are welded together and form a single module
- Low weight makes the jack an ideal solution for use in remote areas (f.e. track lifting for maintenance reasons).



Typ U6
Model U6

Einsatzmöglichkeit
Application

| Technische Daten <i>Technical data</i> | U6 |
|--|----------------------|
| Artikelnummer <i>item number</i> | 13292 |
| Volltraglast <i>full load capacity</i> | 60 kN (6 t) |
| Arbeitsdruck <i>working pressure</i> | 720 bar |
| Kleinste Ansetzhöhe mittels Sicherheits-Hebelasche <i>minimum loading height using safety toe</i> | 18 mm |
| Hubhöhe <i>lifting height</i> | 115 mm |
| Verstellbarkeit der Sicherheits-Hebelasche <i>adjustable range of safety toe</i> | - |
| Größe der Kopfplatte <i>size of top plate</i> | 117 x 146 mm |
| Außenmaße (L x B x H) <i>overall dimensions (L x W x H)</i> | 256 x 146x 263 mm |
| Eigengewicht mit Ölfüllung <i>tare weight incl. oil fill</i> | 15 kg |