

Trolley clamp model CTP

Capacity 1000 - 3000 kg

Easy fitting to overhead beams for the attachment and transport of loads.

Features

Central threaded spindle provides quick adjustment to the required beam width.

Threaded spindle and clevis are zinc-plated for added corrosion protection.



Technical data model CTP

| Model | EAN-No. 4025092* | Capacity kg | Beam flange width b mm | Min. curve radius m | Weight kg |
|---------|---------------------|----------------|------------------------------|---------------------------|--------------|
| CTP 1-A | *063012 | 1000 | 60 - 150 | 0.6 | 2.5 |
| CTP 2-A | *055437 | 2000 | 75 - 200 | 0.9 | 9.9 |
| CTP 2-B | *055444 | 2000 | 200 - 300 | 0.9 | 10.3 |
| CTP 3-A | *055451 | 3000 | 75 - 200 | 1.15 | 17.5 |
| CTP 3-B | *055468 | 3000 | 200 - 320 | 1.15 | 19.5 |

Dimensions model CTP

| Model | CTP 1-A | CTP 2-A | CTP 2-B | CTP 3-A | CTP 3-B |
|------------|---------|---------|---------|---------|---------|
| A, mm | 82-109 | 106-155 | 136-191 | 128-171 | 150-212 |
| D, mm | 26 | 42 | 42 | 50 | 50 |
| E, mm | 22 | 20 | 20 | 22 | 22 |
| H1, mm | 20 | 24 | 24 | 30.5 | 30.5 |
| I, mm | 53 | 71.5 | 71.5 | 95.5 | 95.5 |
| L, mm | 160 | 260 | 260 | 310 | 310 |
| L1, mm | 75 | 130 | 130 | 150 | 150 |
| M, mm | M12 | M18 | M18 | M24 | M24 |
| O, mm | 46 | 60 | 60 | 80 | 80 |
| P, mm | 153 | 205 | 255 | 220 | 280 |
| T, mm | 105 | 139 | 189 | 155 | 215 |
| t max., mm | 15 | 25 | 25 | 25 | 25 |