

Geared type model HTG

Capacity 500 - 20000 kg

The trolley enables the exact positioning or easy traversing of large loads. It has excellent rolling features due to machined steel wheels mounted on prelubricated, encapsulated ball bearings. The wheels are designed for a max. beam profile incline of 14%.



Features

- Adjustable to fit a wide range of beam widths and profiles.
- Wheel fracture supports and anti-tilt devices are standard.

Optional

- Buffers
- Locking device to secure the unloaded trolley in parking position.
- Rust and acid resistant hand chains.
- Corrosion resistant version.
- Spark resistant equipment.

Model	EAN-No. 4025092*	Capacity kg	Size	Beam flange width b mm	Max. flange thickness t mm	Min. curve radius m	Effort at WLL kg	Net weight* kg	Net weight** with beam brake kg
HTG 500	*074711	500	A	50 - 220	25	0.9	3	9.7	16.2
HTG 1000	*074728	1000	A	50 - 220	25	0.9	6	11.2	19.2
HTG 2000	*074735	2000	A	66 - 220	25	1.15	7	18.0	26.0
HTG 3000	*074742	3000	A	74 - 220	25	1.4	7	35.4	44.6
HTG 5000	*074759	5000	A	90 - 220	25	1.8	9	51.8	62.3
HTG 500	*074766	500	B	160 - 300	40	0.9	3	12.6	19.1
HTG 1000	*074841	1000	B	160 - 300	40	0.9	6	14.1	22.1
HTG 2000	*074773	2000	B	160 - 300	40	1.15	7	21.3	29.3
HTG 3000	*074780	3000	B	160 - 300	40	1.4	7	39.2	48.4
HTG 5000	*074797	5000	B	180 - 300	40	1.8	9	56.0	66.5
HTG 8000	*074803	8000	B	125 - 310	40	1.8	14	104.0	-
HTG 10000	*074810	10000	B	125 - 310	40	1.8	14	104.0	-
HTG 15000	*074827	15000	B	125 - 310	40	5.0	29	230.0	-
HTG 20000	*074834	20000	B	125 - 310	40	5.0	29	230.0	-