

ETC Openklapbaar blok "off-shore model" uitgevoerd met haak, voor intensief gebruik



- Eenvoudig te monteren
- Lichtgewicht
- Losse onderdelen beveiligd tegen verlies

	Ø schijf dog*/Ø buitenkant schijf (mm)	Ø staaldraad min/max (mm)	W.L.L. (t)	Gewicht (kg)
ETC2-79E10	60/79	9/10	2	2.7
ETC5-114E14	90/114	12/14	5	8
ETC5-165E14	140/165	12/14	5	10.5
ETC8-142E19	112/142	17/19	8	15
ETC8-209E19	177/209	17/19	8	20
ETC8-262E19	221/262	17/19	8	25
ETC8-326E23	275/326	20/23	8	29
ETC12-145E23	112/145	20/23	12.5	30
ETC12-216E23	174/216	20/23	12.5	35
ETC12-216E29	174/216	26/29	12.5	35
ETC15-262E23	221/262	20/23	15	38
ETC15-326E23	275/326	20/23	15	45
ETC15-420E23	355/420	20/23	15	65
ETC20-216E29	174/216	26/29	20	39
ETC20-268E38	224/268	35/38	20	56
ETC20-410E38	349/410	35/38	20	70
ETC25-262E29	221/262	26/29	25	62
ETC25-326E29	270/326	26/29	25	85
ETC32-334E46	270/334	42/46	32	95
ETC32-518E46	443/518	42/46	32	135

* dog: diameter onderin de groef