


Turnbuckles with trapezoid thread

Stock No.	WLL (t)	L min (mm)	L max (mm)	Take-up (mm)	Thread (trap.)	Dimensions (mm)								Weight (kg)
						A	J	K	L	P	U	V	W	
41.001.00.12	1	376	544	168	18 x 4	220	12	21	48	16	50	17.5	19	2
41.001.60.12	1.6	417	605	188	22 x 5	240	16	26	58	20	55	22.5	23	3
41.002.00.12	2	441	641	200	24 x 5	260	16	26	58	22	58	25	26	4
41.002.50.12	2.5	522	728	206	28 x 5	280	20	32	72	24	73	27.5	30	6
41.003.10.12	3.1	548	776	228	30 x 6	300	20	32	72	27	80	30	32	7
41.004.00.12	4	602	843	241	32 x 6	320	25	40	94	30	86	32.5	35	10
41.005.00.12	5	634	874	240	36 x 6	340	25	40	94	36	93	37.5	40	14
41.006.30.12	6.3	724	987	263	44 x 7	380	30	45	108	39	108	42.5	45	20
41.008.00.12	8	778	1075	297	48 x 8	420	32	50	115	45	112	47.5	50	29
41.010.00.12	10	842	1151	309	52 x 8	460	36	60	125	48	115	55	60	37
41.012.60.12	12.6	925	1265	340	55 x 9	500	40	65	144	52	122	60	65	48
41.016.00.12	16	1009	1363	354	65 x 10	540	45	70	163	60	130	65	70	66
41.020.00.12	20	1097	1479	382	70 x 10	580	55	75	173	68	145	70	75	81
41.025.00.12	25	1177	1581	404	75 x 10	620	60	80	192	72	160	75	80	94
41.031.50.12	31.5	1276	1716	440	80 x 10	660	60	90	216	80	175	85	90	135

Minimum Ultimate Strength = 5 x WLL.

Standard painted blue, but can be supplied in any color or galvanized.
 Factory supplied with lock nuts. Lock plates or special locking devices possible.
 Can be supplied with turning wheel or ratchet. Other sizes possible.
 Straight or in-line pull only.