


**Turnbuckles with trapezoid thread**

Stock No.	WLL (t)	L min (mm)	L max (mm)	Take-up (mm)	Thread (trap.)	Dimensions (mm)							Weight (kg)	
						A	P	Q	S	T	U	V		W
41.001.00.13	1	333	501	168	18 x 4	220	16	18	17.5	16	50	18	19	1.5
41.001.60.13	1.6	367	555	188	22 x 5	240	20	23	22.5	20	55	22	23	2
41.002.00.13	2	395	595	200	24 x 5	260	22	25	25	22	58	25	26	3
41.002.50.13	2.5	459	665	206	28 x 5	280	24	27	27.5	25	73	27	30	5
41.003.10.13	3.1	488	716	228	30 x 6	300	27	30	30	28	80	30	32	7
41.004.00.13	4	521	762	241	32 x 6	320	30	33	32.5	30	86	32	35	9
41.005.00.13	5	561	801	240	36 x 6	340	36	39	37.5	35	93	37	40	13
41.006.30.13	6.3	636	899	263	44 x 7	380	39	42	42.5	40	108	42	45	18
41.008.00.13	8	689	986	297	48 x 8	420	45	48	47.5	45	112	47	50	27
41.010.00.13	10	748	1057	309	52 x 8	460	48	52	55	50	115	55	60	35
41.012.60.13	12.6	812	1152	340	55 x 9	500	52	56	60	55	122	60	65	44
41.016.00.13	16	883	1237	354	65 x 10	540	60	65	65	60	130	65	70	61
41.020.00.13	20	957	1339	382	70 x 10	580	68	74	70	65	145	70	75	74
41.025.00.13	25	1026	1430	404	75 x 10	620	72	78	75	70	160	75	80	86
41.031.50.13	31.5	1105	1535	430	80 x 10	660	80	86	85	80	175	85	90	125
41.040.00.13	40	1230	1725	495	90 x 10	695	90	96	95	90	190	92	100	156
41.050.00.13	50	1335	1885	550	100 x 10	770	100	106	105	100	205	102	110	200
41.063.00.13	63	1463	2068	605	110 x 10	845	110	116	115	110	220	112	120	290
41.080.00.13	80	1594	2254	660	120 x 10	920	125	131	135	125	235	127	140	350
41.100.00.13	100	1702	2417	715	130 x 10	995	140	146	148	140	250	142	156	440
41.125.00.13	125	1838	2608	770	140 x 10	1070	160	168	168	160	270	162	176	660
41.160.00.13	160	2056	2936	880	160 x 10	1220	180	188	190	180	290	182	200	925

Minimum Ultimate Strength = 5 x WLL.

Standard painted blue, but can be supplied in any color or galvanized.  
 Factory supplied with lock nuts. Lock plates or special locking devices possible.  
 Can be supplied with turning wheel or ratchet. Other sizes possible.  
 Straight or in-line pull only.