


**Turnbuckles with trapezoid thread**

Stock No.	WLL (t)	L min (mm)	L max (mm)	Take-up (mm)	Thread (trap.)	Dimensions (mm)							Weight (kg)
						A	J	K	L	Q	S	T	
41.001.00.23	1	355	523	168	18 x 4	220	12	21	48	18	17.5	16	1.5
41.001.60.23	1.6	400	588	188	22 x 5	240	16	26	58	23	22.5	20	2
41.002.00.23	2	424	624	200	24 x 5	260	16	26	58	25	25	22	3
41.002.50.23	2.5	475	681	206	28 x 5	280	20	32	72	27	27.5	25	5
41.003.10.23	3.1	498	726	228	30 x 6	300	20	32	72	30	30	28	7
41.004.00.23	4	554	795	241	32 x 6	320	25	40	94	33	32.5	30	9
41.005.00.23	5	585	825	240	36 x 6	340	25	40	94	39	37.5	35	12
41.006.30.23	6.3	665	928	263	44 x 7	380	30	45	108	42	42.5	40	17
41.008.00.23	8	724	1021	297	48 x 8	420	32	50	115	48	47.5	45	25
41.010.00.23	10	797	1106	309	52 x 8	460	36	60	125	52	55	50	33
41.012.60.23	12.6	875	1215	340	55 x 9	500	40	65	144	56	60	55	42
41.016.00.23	16	966	1320	354	65 x 10	540	45	70	163	65	65	60	58
41.020.00.23	20	1044	1426	382	70 x 10	580	55	75	173	74	70	65	71
41.025.00.23	25	1119	1523	404	75 x 10	620	60	80	192	78	75	70	82
41.031.50.23	31.5	1211	1641	430	80 x 10	660	60	90	216	86	85	80	119

Minimum Ultimate Strength = 5 x WLL.

Standard painted blue, but can be supplied in any color or galvanized.  
 Factory supplied with lock nuts. Lock plates or special locking devices possible.  
 Can be supplied with turning wheel or ratchet. Other sizes possible.  
 Straight or in-line pull only.