


Turnbuckles with trapezoid thread

Stock No.	WLL (t)	L min (mm)	L max (mm)	Take-up (mm)	Thread (trap.)	Dimensions (mm)			Weight (kg)
						A	B	D	
41.001.00.55	1	282	462	180	18 x 4	220	20	20	2
41.001.60.55	1.6	310	530	220	22 x 5	240	25	25	3
41.002.00.55	2	336	550	214	24 x 5	260	28	25	4
41.002.50.55	2.5	368	593	225	28 x 5	280	32	32	6
41.003.10.55	3.1	394	633	239	30 x 6	300	35	32	7
41.004.00.55	4	427	676	249	32 x 6	320	40	35	9
41.005.00.55	5	460	704	244	36 x 6	340	45	40	12
41.006.30.55	6.3	519	792	273	44 x 7	380	50	45	16
41.008.00.55	8	569	870	301	48 x 8	420	55	50	24
41.010.00.55	10	625	928	303	52 x 8	460	60	55	32
41.012.60.55	12.6	678	1026	348	55 x 9	500	65	60	42
41.016.00.55	16	750	1112	362	65 x 10	540	75	70	58
41.020.00.55	20	800	1200	400	70 x 10	500	80	75	73
41.025.00.55	25	858	1278	420	75 x 10	540	85	80	82
41.031.50.55	31.5	920	1354	430	80 x 10	660	90	90	118

Minimum Ultimate Strength = 5 x WLL.

Testing and certification not possible. Standard painted blue, but can be supplied in any color or galvanized.

Available in all combinations of jaws, oval eyes and stud eyes. Factory supplied with lock nuts.

Lock plates or special locking devices possible. Can be supplied with turning wheel or ratchet. Other sizes possible.

Straight or in-line pull only.