

Chain Classic grade 8 EN 818-2 Short link chain, KL



Heat treatment

Quenched and tempered.

Surface treatment

Painted black (B)

Marking

8EG

Art.no Box	Code	D nom. mm	L mm	E mm	Weight kgs/m	WLL tonnes	Manufacturing proof force kN	Breaking force kN
Z802174 - 1 x 200 m	KLB 6-8E	6	18	8.5	0.8	1.12	28.3	45.2
Z802175 - 1 x 200 m	KLB 7-8E	7	21	10	1.1	1.5	38.5	61.6
Z802176 - 1 x 100 m	KLB 8-8E	8	24	11	1.4	2	50.3	80.4
Z802156 - 1 x 100 m	KLB 10-8E	10	30	14	2.2	3.15	78.5	126
Z802157 - 1 x 100 m	KLB 13-8E	13	39	18	3.7	5.3	133	212
Z802177 - 1 x 100 m	KLB 16-8E	16	48	22	5.6	8	201	322
Z801203 - 1 x 100 m	KLB 19-8E	19	57	26	7.8	11.2	284	454
Z801228 - 1 x 50 m	KLB 22-8E	22	66	30	10.6	15	380	608
Z801231 - 1 x 25 m	KLB 26-8E	26	78	35	14.8	21.2	531	849
Z801232 - 1 x 25 m	KLB 32-8E	32	96	43	21.6	31.5	804	1290