




## MTS

### Master link assembly

**Norm EN 1677-4**


Code	Chain Ø β			Dimensions in mm								WLL	BF	Weight
	30°	45°	60°	A	B	Ø C	E	a	b	Dia	t	t	Kg	
MTS 16	-	6	6/7	120	70	16	6.7	100	60	13	2.5	10.0	1.20	
MTS 18	6	7	8	135	75	18	7.4	100	60	16	3.5	14.0	1.80	
MTS 22	7/8	8	10	150	90	22	8.9	120	70	18	6.5	26.0	2.90	
MTS 25	10	10	13	170	95	25	10.6	120	70	20	8.5	34.0	3.90	
MTS 28	-	-	-	200	120	28	11.0	120	70	20	10.0	40.0	4.90	
MTS 30	-	13	16	200	120	30	13.4	135	75	22	13.0	52.0	6.00	
MTS 36	13	116	18/19	250	150	36	16.6	135	75	25	17.0	68.0	9.60	
MTS 38	-	-	20	250	150	38	17.1	170	95	28	20.0	80.0	12.60	
MTS 44*	16/18	18/19/20	22	280	170	44	18.0	200	120	33	27.0	108.0	19.70	
MTS 45*	19	-	-	300	200	45	20.0	200	120	36	30.0	120.0	22.50	
MTS 50*	20/22	22	26	300	200	50	21.0	150	90	38	40.0	160.0	24.50	
MTS 55*	-	26	32	300	200	55	23.0	150	90	38	50.0	200.0	28.00	
MTS 58**	26	-	-	350	200	58	-	150	90	42	60.0	240.0	34.60	
MTS 70**	-	32	-	400	250	70	-	300	150	55	80.0	320.0	74.70	
MTS 80**	32	-	-	400	250	80	-	300	150	58	100.0	400.0	92.40	

\* unpainted.

\*\* without flat and unpainted.