




AL Eye bolt

Our extensive range of alloy steel lifting eyes, incorporates 22 different ISO standard threads. Other special threads such as UNC, Whitworth, etc. are available on request.

These lifting eyes can be used only in their axis (angle must be less than 30°), never in oblique. This length makes the use of a grade 8 nut possible.

WLL is stamped on the bodies. The minimum factor of safety is 5:1.



Code	WLL	Ø ISO M x Pitch mm	Unma- chined Ø	Dimensions in mm				BF t	Weight Kg
				A	B	L	C		
AL 6	0.20	M6 x 1.00	12	18	20	20	6	1.0	0.05
AL 8	0.40	M8 x 1.25	12	16	20	24	7	2.0	0.05
AL 10	0.70	M10 x 1.50	14	19	22	30	8	3.5	0.07
AL 12	1.00	M12 x 1.75	16	23	27	36	10	5.0	0.13
AL 14	1.20	M14 x 2.00	18	28	30	40	14	6.0	0.24
AL 16	1.50	M16 x 2.00	22	30	35	55	14	7.5	0.36
AL 18	2.00	M18 x 2.50	22	30	35	54	14	10.0	0.38
AL 20	2.50	M20 x 2.50	26	34	40	59	16	12.5	0.55
AL 22	3.00	M22 x 2.50	29	38	45	66	19	15.0	0.73
AL 24	4.00	M24 x 3.00	30	40	55	84	20	20.0	1.08
AL 27	5.00	M27 x 3.00	30	42	55	81	20	25.0	1.18
AL 30	6.00	M30 x 3.50	40	49	60	100	24	30.0	1.87
AL 33	7.00	M33 x 3.50	40	49	60	100	24	35.0	1.99
AL 36	8.00	M36 x 4.00	41	45	68	118	25	40.0	2.44
AL 39	9.00	M39 x 4.00	41	45	68	118	25	45.0	2.58
AL 42	10.00	M42 x 4.50	50	56	80	135	31	50.0	3.97
AL 45	15.00	M45 x 4.50	50	56	80	135	31	75.0	4.23
AL 48	18.00	M48 x 5.00	72	63	97	145	42	90.0	8.33
AL 52	20.00	M52 x 5.00	72	63	97	145	42	100.0	8.80
AL 56	25.00	M56 x 5.50	72	63	97	145	42	125.0	9.00
AL 60	30.00	M60 x 5.50	72	63	97	145	42	150.0	9.50
AL 64	36.00	M64 x 6.00	72	63	97	145	42	180.0	9.75