




## EL Eye nut

These eye nuts are Grade 8 alloy steel and have a flat section that is designed to accommodate omega links (code CO). They have ISO metric threads as standard, however other thread types can be supplied on request. (UNC, Whitworth)



Code	Type	WLL	Ø ISO	Dimensions in mm				BF	Weight
		t	M x Pitch	A	B	C	D	t	
EL 6	5/6	0.20	M6 x 1.00	45	30	11	16	1.0	0.15
EL 8	5/6	0.40	M8 x 1.25	45	30	11	16	2.0	
EL 10	5/6	0.70	M10 x 1.50	45	30	11	16	3.5	
EL 12	7/8	1.00	M12 x 1.75	48	32	12	17	5.0	0.25
EL 14	7/8	1.20	M14 x 2.00	48	32	12	17	6.0	
EL 16	10	1.50	M16 x 2.00	60	37	14	18	7.5	0.40
EL 18	10	2.00	M18 x 2.50	60	37	14	18	10.0	
EL 20	10	2.50	M20 x 2.50	60	37	14	18	12.5	
EL 22	13	3.00	M22 x 2.50	75	48	16	23	15.0	
EL 24	13	4.00	M24 x 3.00	75	48	16	23	20.0	0.67
EL 27	13	5.00	M27 x 3.00	75	48	16	23	25.0	
EL 30	16	6.00	M30 x 3.50	88	58	19	28	30.0	1.20
EL 33	16	7.00	M33 x 3.50	88	58	19	28	35.0	
EL 36	18/20	8.00	M36 x 4.00	105	73	24	42	40.0	1.50
EL 39	18/20	9.00	M39 x 4.00	105	73	24	42	45.0	
EL 42	18/20	10.00	M42 x 4.50	105	73	24	42	50.0	
EL 45	22	15.00	M45 x 4.50	121	82	25	43	75.0	3.00
EL 48	22	18.00	M48 x 5.00	121	82	25	43	90.0	

Safety factor 5.