




## ALS

### Safety lifting eye

These eye nuts are Grade 8 alloy steel. They rotate 360°. You have to screw them with a dynamometric key. The cylindrical head of the screw prevents any catch by rotation of the eye nut. They have a flat section that is designed to accommodate omega links (code CO). They have ISO metric threads as standard.



Code	Type	WLL	Ø ISO M x Pitch mm	Dimensions in mm					Hex key	BF	Weight
				A	B	C	D	L			
ALS 8	5/6	0.40	M8 x 1.25	38	30	11	26	17	8	2.0	0.22
ALS 10	5/6	0.70	M10 x 1.50	36	30	11	28	17	8	3.5	0.24
ALS 12	7/8	1.00	M12 x 1.75	37	32	12	31	21	8	5.0	0.30
ALS 14	7/8	1.20	M14 x 2.00	35	32	12	33	26	8	6.0	0.45
ALS 16	10	1.50	M16 x 2.00	43	37	14	40	26	10	7.5	0.53
ALS 18	10	2.00	M18 x 2.50	41	37	14	42	26	10	10.0	0.68
ALS 20	13	2.50	M20 x 2.50	53	48	16	50	30	12	12.5	0.72
ALS 22	13	3.00	M22 x 2.50	51	48	16	52	35	12	15.0	1.20
ALS 24	16	4.00	M24 x 3.00	64	58	19	57	37	14	20.0	1.80
ALS 27	16	5.00	M27 x 3.00	61	58	19	60	47	14	25.0	1.90