

VERBINDINGSSCHALMEN - Type Framlok

| Type | WL in tf | D1 | D2 in mm | L | B | Voor ketting | Gewicht in kg |
|--------|-------------|----|-------------|-----|----|-----------------|------------------|
| fl 3 | 2.0 | 8 | 15 | 28 | 15 | 7-8 | 0.1 |
| fl 4 | 2.0 | 8 | 15 | 33 | 19 | 7-8 | 0.1 |
| fl 6 | 3.2 | 10 | 22 | 37 | 21 | 7- 8-10 | 0.2 |
| fl 7 | 3.75 | 11 | 22 | 36 | 19 | 8-10-11 | 0.2 |
| fl 8 | 3.75 | 11 | 22 | 39 | 22 | 8-10-11 | 0.2 |
| fl 9 | 5.4 | 13 | 25 | 45 | 24 | 10-11-13 | 0.4 |
| fl 10 | 5.4 | 13 | 25 | 48 | 28 | 10-11-13 | 0.4 |
| fl 11 | 8.0 | 16 | 30 | 54 | 28 | 13-16 | 0.6 |
| fl 12 | 8.0 | 16 | 30 | 61 | 35 | 13-16 | 0.7 |
| fl 13 | 12.5 | 20 | 38 | 63 | 30 | 16-20 | 1.2 |
| fl 14* | 12.5 | 20 | 38 | 72 | 40 | 16-20 | 1.3 |
| fl 15* | 15.5 | 22 | 42 | 70 | 34 | 20-22 | 1.5 |
| fl 16* | 15.5 | 22 | 42 | 83 | 48 | 20-22 | 1.8 |
| fl 17* | 20.0 | 25 | 47 | 75 | 36 | 20-22-25 | 2.2 |
| fl 19* | 25.0 | 28 | 52 | 84 | 43 | 22-25-28 | 3.1 |
| fl 20* | 25.0 | 28 | 52 | 98 | 54 | 22-25-28 | 3.5 |
| fl 21* | 32.0 | 32 | 60 | 97 | 44 | 25-28-32 | 4.5 |
| fl 22* | 32.0 | 32 | 60 | 103 | 54 | 25-28-32 | 4.9 |
| fl 23* | 32.0 | 32 | 60 | 125 | 73 | 25-28-32 | 5.6 |

