



G-4154


Green Pin® Trawling Shackles

dee shackles with square headed screw pin

- **Material** : bow and pin high tensile steel, Grade 6, quenched and tempered
- **Safety Factor** : MBL equals 6 x WLL
- **Standard** : meets performance requirements of US Fed. Spec. RR-C-271, Grade A
- **Finish** : hot dipped galvanized
- **Certification** : at no extra charges this product can be supplied with a works certificate, certificate of basic raw material, manufacturer test certificate and/or EC Declaration of Conformity

working load limit	diameter bow	diameter pin	diameter eye	width eye	width inside	length inside	length	length bolt	width bolt head	weight each
tons	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	kg
2	13.5	16	34	13.5	22	43	85	58	22	0.32
3.25	16	19	40	16	27	51	105	71	27	0.58
4.75	19	22	47	19	31	59	125	82	32	0.92
6.5	22	25	53	22	36	73	144	93	32	1.33
8.5	25	28	60	25	43	85	161	108	36	2.03
9.5	28	32	67	28	47	90	179	120	41	2.88
12	32	35	74	32	51	94	199	137	50	3.96
13.5	35	38	80	35	57	115	220	149	50	5.24
17	38	42	89	38	60	127	239	164	60	6.8
25	45	50	104	45	74	149	283	192	60	11.22

In inch

working load limit	diameter bow	diameter pin	diameter eye	width eye	width inside	length inside	length	length bolt	width bolt head	weight each
tons	a inch	b inch	c inch	d inch	e inch	f inch	g inch	h inch	i inch	lbs
2	1/2	5/8	1 11/32	17/32	7/8	1 23/32	3 11/32	2 9/32	7/8	0.7
3.25	5/8	3/4	1 19/32	5/8	1 3/32	2	4 1/8	2 25/32	1 3/32	1.28
4.75	3/4	7/8	1 7/8	3/4	1 1/4	2 5/16	4 29/32	3 1/4	1 9/32	2.03
6.5	7/8	1	2 3/32	7/8	1 7/16	2 7/8	5 11/16	3 11/16	1 9/32	2.93
8.5	1	1 1/8	2 11/32	1	1 23/32	3 11/32	6 5/16	4 1/4	1 7/16	4.48
9.5	1 1/8	1 1/4	2 5/8	1 1/8	1 7/8	3 9/16	7 1/32	4 3/4	1 5/8	6.35
12	1 1/4	1 3/8	2 29/32	1 9/32	2	3 23/32	7 13/16	5 3/8	1 31/32	8.72
13.5	1 3/8	1 1/2	3 5/32	1 3/8	2 1/4	4 17/32	8 11/16	5 7/8	1 31/32	11.56
17	1 1/2	1 5/8	3 1/2	1 17/32	2 11/32	5	9 3/8	6 1/2	2 11/32	15
25	1 3/4	2	4 1/8	1 25/32	2 29/32	5 7/8	11 5/32	7 9/16	2 11/32	24.74