

Hand pallet truck HU with weighing system model HU PW 25 T

Capacity 2500 kg

Fitted with four high quality load cells the hand pallet truck becomes a mobile weighing system.

Features

- The basic truck is the Little Mule® hand pallet truck HU Profi with a pallet entry height of only 85 mm.
- LED display (83plus)* has 6 characters; the characters are 20 mm in height.
- Weighing operations: Tare (gross/net), count, add, automatic return to zero.
- Accuracy is $\pm 0.1\%$ of the end value.
- The readings start at 1.0 kg.
- The battery capacity provides for around 28 operating hours.
- The weighing system is calibrated at the factory.



Optional

- Stainless steel version
- Special calibration of the measured value (Multi-range scale).
- With printer
- Change setting of partition.

Technical data model HU PW 25 T

Model	HU PW 25 T	HU PW 25 TR - 83plus with printer
EAN-No. 4025092*	*252683	*253130
Capacity Q, kg	2500	2500
Load center c, mm	600	600
Load distance x, mm	850	850
Wheelbase y, mm	1205	1205
Weight, kg	145	145
Axle loading with load front/rear, kg	409/1735	409/1735
Axle loading without load front/rear, kg	86/59	86/59
Tyre type front/rear**	PUR/PA	PUR/PA
Overall width b1/b2, mm	535	535
Outside dimension of forks b5, mm	535	535
Fork dimensions s/e/l, mm	60 x 165 x 1140	60 x 165 x 1140
Ground clearance, wheelbase centre m2, mm	20	20
Aisle width pallet 800 x 1200, longitudinal Ast, mm	1832	1832
Turning circle radius Wa, mm	1367	1367
Tyre size front, mm	194 x 50	194 x 50
Tyre size rear, mm	80 x 63	80 x 63
Number of wheels front/rear	2/4	2/4
Track width front, mm	135	135
Track width rear, mm	370	370
Stroke h3, mm	115	115
Height of control handle in operation max. h14, mm	1230	1230
Height lowered h13, mm	85	85
Overall length l1, mm	1525	1525
Length incl. apron l2, mm	375	375

** PA...Polyamide, PUR...Polyurethane, VG...Solid rubber, S...Steel

S...Single, T...Tandem