

Dyneema

Technische specificaties

| | |
|--------------------|--|
| Soortelijk gewicht | 0.97 |
| Smeltpunt | 150 °C |
| Rekpercentage | 4% |
| Kleur | Wit |
| Constructie | 8 en 12-strengs gevlochten "Leomax" |



| Diameter mm. | Gewicht Kg/100m zonder coating | breekkracht | |
|-----------------|--------------------------------------|---------------------|---------------------|
| | | Dyneema SK60 Ton | Dyneema SK75 Ton |
| 16 | 12.3 | 20.3 | 23.9 |
| 18 | 16.5 | 26.9 | 31.7 |
| 20 | 21.0 | 33.7 | 39.7 |
| 22 | 25.2 | 40.1 | 47.1 |
| 24 | 27.0 | 42.5 | 50.0 |
| 28 | 37.5 | 57.7 | 67.9 |
| 32 | 50.1 | 75.4 | 88.7 |
| 36 | 62.5 | 92 | 108 |
| 40 | 75.0 | 108.6 | 128 |
| 44 | 87.1 | 127 | 146 |
| 48 | 104 | 147 | 169 |
| 52 | 116 | 164 | 189 |
| 56 | 142 | 193 | 222 |
| 60 | 158 | 210 | 242 |
| 64 | 174 | 237 | 273 |
| 68 | 199 | 262 | 301 |
| 72 | 224 | 297 | 342 |
| 76 | 249 | 330 | 380 |
| 80 | 274 | 361 | 415 |