

Manilla

Technische specificaties

Constructie: 3-strengs



Diameter mm.	Omtrek inches	Gewicht % mtr.	Min. breekkraft Kgf.	Min. breekkraft kN.
8	1	5.5	480	4.70
10	1 1/4	6.8	635	6.22
12	1 1/2	10.5	950	9.31
14	1 3/4	14.1	1280	12.5
16	2	19.1	1780	17.4
18	2 1/4	22.3	2130	20.8
20	2 1/2	27.7	2840	27.8
22	2 3/4	33.2	3400	33.3
24	3	40.0	4060	39.8
26	3 1/4	46.8	4720	46.2
28	3 1/2	53.6	5330	52.2
30	3 3/4	62.7	6100	59.8
32	4	70.5	6860	67.2
34	4 1/4	80.0	7620	74.7
36	4 1/2	89.5	8640	84.7
38	4 3/4	100	9400	92.1
40	5	111	10400	101.9
44	5 1/2	135	12700	124.5
48	6	160	14700	144.1
52	6 1/2	188	17300	169.6
56	7	218	19800	194.1
60	7 1/2	250	22600	221.5
64	8	290	25700	251.9
68	8 1/2	321	28700	281.3
72	9	360	32000	313.7
80	10	444	39100	383.3
88	11	538	47200	462.7
96	12	639	55900	548.0