

Nylon

Technische specificaties

Soortelijk gewicht	1.14
Smeltpunt	210 °C
Rekpercentage	50%
Kleur	Wit
Constructie	3-strengs geslagen of 8- en 12-strengs gevlochten "Leomax"



Diameter mm.	Circumference inches	Weight % mtr.	Minimum breaking load Kgf.	Minimum breaking load kN.
8	1	4.0	1350	13.2
10	1 1/4	6.3	2080	20.3
12	1 1/2	9.0	3000	29.4
14	1 3/4	12.3	4100	40.2
16	2	16.0	5300	51.9
18	2 1/4	20.3	6700	65.6
20	2 1/2	25.0	8300	81.3
22	2 3/4	30.3	10000	98.0
24	3	36.0	12000	117.6
26	3 1/4	42.3	13800	135.2
28	3 1/2	49.0	15800	154.9
30	3 3/4	56.3	17800	174.5
32	4	64.0	20000	196.0
34	4 1/4	72.3	22300	218.6
36	4 1/2	81.0	24800	243.1
38	4 3/4	90.3	27300	267.6
40	5	100	30000	294.1
44	5 1/2	121	35800	350.9
48	6	144	42000	411.7
52	6 1/2	169	48800	478.4
56	7	196	56000	549.0
60	7 1/2	225	63800	625.4
64	8	256	72000	705.8
68	8 1/2	289	80750	791.6
72	9	324	90000	882.3
80	10	400	110000	1078.4
88	11	484	131000	1284.3
96	12	576	154000	1509.8
104	13	676	182000	1784.3
112	14	784	210000	2058.8
120	15	900	240000	2352.9
128	16	1024	272000	2666.6
136	17	1156	306000	3000.0
144	18	1296	342000	3352.9
152	19	1444	380000	3725.4
160	20	1600	420000	4117.